

Dingli Scissor Lifts Product Manuals



Electric



Engine




DINGLI[®]
Exceed · New Height



Self-propelled Scissor Lifts(Electric Pint-sized Type)

Model: **JCPT1614AC/HA - JCPT1612AC/HA - JCPT1612AC/HA - JCPT1612ACS/HAS - JCPT1412AC/HA - JCPT1212AC/HA - JCPT1012AC/HA - JCPT1008AC/HA - JCPT0808AC/HA - JCPT0807AC/HA**

Electric Pint-sized scissor lifts series uses the battery as the power source, and has two types of AC motor drive and hydraulic motor drive. The maximum working height covers 7.8-15.7m and the maximum load is 450kg. This type of scissor lifts has the advantages of energy saving, environmental protection, zero emissions, no noise, which is suitable for indoor flat ground and higher environmental requirements of the working environment.



Easy Maintenance



Non Marking Tyre



Folding Guardrails



Extended Platform

Model =Electric	JCPT0807AC
--	-------------------

Size	
-------------	--

Max. Working Height	7.80m
Max. Platform Height	5.80m
Overall Length	1.86m
Overall Width	0.76m
Overall Height(Rails Up)	2.15m
Overall Height(Rails Down)	1.83m
Platform Size(Length×Width)	1.67×0.74m
Platform Extension Size	0.90m
Ground Clearance(Stowed/Raised)	0.09m/0.016m
Wheelbase	1.36m
Turning Radius(Inside/Outside)	0m/1.64m
Tyres	Φ323×100mm

Performance	
--------------------	--

S.W.L	230kg
S.W.L On Extension	113kg
Max. Occupants	2
Gradeability	25%
Max. Working Slope	1.5°/3°
Travel Speed(Stowed)	0.6km/h
Travel Speed(Raised)	4.5km/h
Up/Down Speed	18/26sec

Weight	
---------------	--

Overall Weight	1630kg
Overall Weight	1580kg

Power	
--------------	--

Battery	4×6V/170Ah
Charger	24V/30A
Driving Motor	2×24VAC/0.5kW
Lifting Motor	24VAC/3kW

Other Configurations			
-----------------------------	--	--	--

Drivable At Full Height	4×2 Driving	Forklift Pockets	Automatic Pothole Protection Device
-------------------------	-------------	------------------	-------------------------------------