

Dingli Scissor Lifts Product Manuals



Electric



Engine




DINGLI[®]
Exceed · New Height



Self-propelled Scissor Lifts(Electric Pint-sized Type)

Model: **JCPT1614AC/HA - JCPT1612AC/HA - JCPT1612AC/HA - JCPT1612ACS/HAS - JCPT1412AC/HA - JCPT1212AC/HA - JCPT1012AC/HA - JCPT1008AC/HA - JCPT0808AC/HA - JCPT0807AC/HA**

Electric Pint-sized scissor lifts series uses the battery as the power source, and has two types of AC motor drive and hydraulic motor drive. The maximum working height covers 7.8-15.7m and the maximum load is 450kg. This type of scissor lifts has the advantages of energy saving, environmental protection, zero emissions, no noise, which is suitable for indoor flat ground and higher environmental requirements of the working environment.



Easy Maintenance



Non Marking Tyre



Folding Guardrails



Extended Platform

Model ■ =Electric	JCPT1012AC		
Size			
Max. Working Height	10.00m		
Max. Platform Height	8.00m		
Overall Length	2.48m		
Overall Width	1.15m		
Overall Height(Rails Up)	2.36m		
Overall Height(Rails Down)	1.83m		
Platform Size(Length×Width)	2.27×1.12m		
Platform Extension Size	0.90m		
Ground Clearance(Stowed/Raised)	0.10m/0.019m		
Wheelbase	1.87m		
Turning Radius(Inside/Outside)	0m/2.20m		
Tyres	φ381×127mm		
Performance			
S.W.L	450kg		
S.W.L On Extension	113kg		
Max. Occupants	2		
Gradeability	25%		
Max. Working Slope	1.5°/3°		
Travel Speed(Stowed)	5km/h		
Travel Speed(Raised)	0.8km/h		
Up/Down Speed	26/33sec		
Weight			
Overall Weight	2710kg		
Overall Weight	2650kg		
Power			
Battery	4×6V/170Ah		
Charger	24V/30A		
Driving Motor	2×24VAC/0.87kW		
Lifting Motor	24VAC/3.5kW		
Other Configurations			
Drivable At Full Height	4×2 Driving	Forklift Pockets	Automatic Pothole Protection Device