

# Dingli Scissor Lifts Product Manuals



Electric



Engine




**DINGLI**<sup>®</sup>  
*Exceed · New Height*



## Self-propelled Scissor Lifts(Electric Pint-sized Type)

Model: **JCPT1614AC/HA - JCPT1612AC/HA - JCPT1612AC/HA - JCPT1612ACS/HAS - JCPT1412AC/HA - JCPT1212AC/HA - JCPT1012AC/HA - JCPT1008AC/HA - JCPT0808AC/HA - JCPT0807AC/HA**

Electric Pint-sized scissor lifts series uses the battery as the power source, and has two types of AC motor drive and hydraulic motor drive. The maximum working height covers 7.8-15.7m and the maximum load is 450kg. This type of scissor lifts has the advantages of energy saving, environmental protection, zero emissions, no noise, which is suitable for indoor flat ground and higher environmental requirements of the working environment.



Easy Maintenance



Non Marking Tyre



Folding Guardrails



Extended Platform

<b>Model</b>	=Electric			<b>JCPT1212AC</b>
<b>Size</b>				
Max. Working Height	12.00m			
Max. Platform Height	10.00m			
Overall Length	2.48m			
Overall Width	1.15m			
Overall Height(Rails Up)	2.49m			
Overall Height(Rails Down)	1.96m			
Platform Size(Length×Width)	2.27×1.12m			
Platform Extension Size	0.90m			
Ground Clearance(Stowed/Raised)	0.10m/0.019m			
Wheelbase	1.87m			
Turning Radius(Inside/Outside)	0m/2.20m			
Tyres	φ381×127mm			
<b>Performance</b>				
S.W.L	320kg			
S.W.L On Extension	113kg			
Max. Occupants	2			
Gradeability	25%			
Max. Working Slope	1.5°/3°			
Travel Speed(Stowed)	5km/h			
Travel Speed(Raised)	0.8km/h			
Up/Down Speed	42/45sec			
<b>Weight</b>				
Overall Weight	3060kg			
Overall Weight	3000kg			
<b>Power</b>				
Battery	4×6V/220Ah			
Charger	24V/30A			
Driving Motor	2×24VAC/0.87kW			
Lifting Motor	24VAC/3.5kW			
<b>Other Configurations</b>				
Drivable At Full Height	4×2 Driving	Forklift Pockets	Automatic Pothole Protection Device	