

Dingli Scissor Lifts Product Manuals



Electric



Engine




DINGLI[®]
Exceed · New Height



Self-propelled Scissor Lifts(Electric Pint-sized Type)

Model: **JCPT1614AC/HA - JCPT1612AC/HA - JCPT1612AC/HA - JCPT1612ACS/HAS - JCPT1412AC/HA - JCPT1212AC/HA - JCPT1012AC/HA - JCPT1008AC/HA - JCPT0808AC/HA - JCPT0807AC/HA**

Electric Pint-sized scissor lifts series uses the battery as the power source, and has two types of AC motor drive and hydraulic motor drive. The maximum working height covers 7.8-15.7m and the maximum load is 450kg. This type of scissor lifts has the advantages of energy saving, environmental protection, zero emissions, no noise, which is suitable for indoor flat ground and higher environmental requirements of the working environment.



Easy Maintenance




Non Marking Tyre



Folding Guardrails



Extended Platform

Model	 =Electric	JCPT1614AC
Size		
Max. Working Height		15.70m
Max. Platform Height		13.70m
Overall Length		2.84m
Overall Width		1.39m
Overall Height(Rails Up)		2.62m
Overall Height(Rails Down)		2.09m
Platform Size(Length×Width)		2.64m×1.12m
Platform Extension Size		0.90m
Ground Clearance(Stowed/Raised)		0.10m/0.019m
Wheelbase		2.22m
Turning Radius(Inside/Outside)		0m/2.70m
Tyres		φ381×127mm
Performance		
S.W.L		227kg
S.W.L On Extension		113kg
Max. Occupants		2
Gradeability		25%
Max. Working Slope		1.5°/3°
Travel Speed(Stowed)		5km/h
Travel Speed(Raised)		0.8km/h
Up/Down Speed		63/71sec
Weight		
Overall Weight		3470kg
Overall Weight		3380kg
Power		
Battery		4×12V/240Ah
Charger		24V/30A
Driving Motor		2x24VAC/0.87kW
Lifting Motor		24VAC/3.5kW
Other Configurations		
Drivable At Full Height	4×2 Driving	Automatic Pothole Protection Device